

SIGNBOOM

WHOLESALE PRINTING

BBF - Blackback Fabric

Product Specs and Care Sheet







Has a white surface with a black coating on the backside making it perfect any application where light blackout is desired including SEG frames, Pop-Ups, Retractable and Banners.

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2	260g/sq.m	7.6 oz/sq.yd.
Base Fabric	DIN 60001	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060	83x83 dtex	75x75 denier
Weave Method	N/A	Warp-knitted 2 bar	
White Point(CIE/D65)	CIE86/ASTME313-00(D65/10,SCI)	≥121	
Dry Heat Shrinkage	N/A	≤3% (transfer , 190°C , 1min)	
Obscuring Ratio	N/A	100%	
Elasticity	N/A	Warp : 3%- 4%	Weft : 4%- 6%
Flame Resistance	/	NFPA 701 , DIN4102-B1	
Recommend Oven Fixation Temperature	N/A	170°C-180°C , 7min	
Calender Fixation Temperature	N/A	190°C , 1min	
Yellowing Temperature	SUPRKC REX-C400	220°C	
Width	ASTM D751-2006	Max 320cm	126"
Standard Length	ASTM D751-2006	50m	55yd

Storage Instructions

Do NOT store damp or wet, the fabric MUST be completely dry before it can be stored. Store in a cool, dry place and ALWAYS roll or very loosely fold so that hard creasing does not occur.

Care Instructions

-  Cold wash only. Delicate cycle. Mild detergent
-  Do not bleach
-  Do not tumble dry
-  Do not dry clean
-  Hang to dry
-  Warm iron or steamer only