

Product Specifications and Care Sheet

SLF - Softlight Fabric

A great all-purpose backlit solution as it is a woven fabric so it won't show pin holes when backlit and still has good depth of colour. As SLF is a woven fabric it can only be trimmed with a hot knife as the fabric will fray if cold cut.







MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	250 g/sq.m	7.3 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Woven	
Shrinkage	N/A	≤2% (210°C, 30s)	
Light Transmittance	ANSI PH2.19, ISO 5/2	(25±5)%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C-210°C, 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30s	≥210°C	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

Storage Instructions

Do NOT store damp or wet, the fabric MUST be completely dry before it can be stored. Store in a cool, dry place and ALWAYS roll or very loosely fold so that hard creasing does not occur.

Care Instructions

-  Cold wash only. Delicate cycle. Mild detergent
-  Do not bleach
-  Do not tumble dry
-  Do not dry clean
-  Hang to dry
-  Warm iron or steamer only